


IF3WL: PVC Wire Harness Tape

Application:

IF3WL is an automobile wire harness tape. To protect the environment and secure end user's health, the PVC backing contains no lead and DEHP. The backing is also free from 13 hazardous substances regulated by JAMA (Japan Automobile Manufacturers Association). The adhesive is our exclusive pressure sensitive water based acrylic adhesive.

Construction:



backing : PVC FILM

adhesive : water based acrylic adhesive

Features:

- Excellent conformability
- Easy to tear
- Good weather ability
- Moderate peeling force
- Easy to operate

Technical Details:

Properties	Average test value
Total Thickness (mm)	0.09±0.02
180° Adhesion to Steel (N/19mm)	2.05
180° Adhesion to backing (N/19mm)	2.09
Tensile Strength(N/19mm)	35.62
Elongation (%)	189
Unwind Force(N/19mm)	3.75

Color: Assorted colors.

Test methods: ASTM D-1000.

Storage condition : 12months when stored in original carton at 73°F(23 °C) and 65 % relative humidity.

Size availability : Standard 10 ~ 25mm (width) X 20 ~ 30M (length). Other sizes are available upon request.

Disclaimer : Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.