

規 格 表

SPECIFICATION

品名Part NO: IH5WL

DATE: 2014. 08. 26

項 目 Items	單 位 Unit	規 格 值 Spec. Value	檢 驗 方 法 Test Method
I. 規格及容許差Dimension & Tolerances:			
§. 紙芯內徑Inside Diameter of roll:	mm	32±1.0	ASTM D-1000
§. 總厚度Total Thickness:	μ m	130±25	
II. 物性與化性Physical & Chemical Prop:			
§. 180° 剝離粘著力180° Peel Adhesion:			
對鋼板To Steel:	kgf/25mm	0.15~0.70	ASTM D-1000
對背面To Backing:	kgf/25mm	0.15~0.70	ASTM D-1000
§. 剝離力Unwind Force:	gf/19mm	200~680	ASTM D-1000
§. 抗張強度Tensile Strength:	kgf/25mm	2.63~6.57	ASTM D-1000
§. 伸長率Elongation:	%	100~300	ASTM D-1000
§. 耐熱性Heat resistance:	hrs	120°C, 120hrs ↑	24026NDS01
§. 破壞電壓Dielectric Breakdown:	kv	3.0 ↑	ASTM D-1000
§. 阻燃性Flammability :		PASS	ASTM D-568
§. RoHS檢測Rohs Test :		PASS	IEC 62321
§. VOC檢測VOC Test :		PASS	GB/T 27630
III. 庫存Storage:			
§. 條件Condition:		23°C , 50%R.H	
§. 有效期限Validity:	Year	1	

IV. 备注Remark:

*客戶須依其實際操作需求與目的, 進行產品測試與確認, 或通知本公司, 以提供進一步諮詢服務。
 Customers need to test and confirm for the actual operational requirements and purpose
 or inform us to supply the further introduction service.

*本表僅供參考, 不可做為驗收標準

Above information is for reference only and should not be as inspection standard.



江苏粘博士新材料有限公司
 A+Value Co., Ltd