

規 格 表

SPECIFICATION

品名Part NO: IW74FL

DATE: 2014. 03. 28

項 目 Items	單 位 Unit	規 格 值 Spec. Value	檢 驗 方 法 Test Method
I. 規格及容許差Dimension & Tolerances:			
§. 紙芯內徑Inside Diameter of roll:	mm	77±1.0	ASTM D-1000
§. 总厚度Total Thickness:	μ m	180±25	
II. 物性與化性Physical & Chemical Prop:			
§. 180° 剝離粘著力180° Peel Adhesion:			
對鋼板To Steel:	kgf/25mm	0.15~0.70	ASTM D-1000
對背面To Backing:	kgf/25mm	0.15~0.70	ASTM D-1000
§. 剝離力Unwind Force:	gf/19mm	200~750	ASTM D-1000
§. 抗張強度Tensile Strength:	kgf/25mm	3.5~12.8	ASTM D-1000
§. 伸長率Elongation:	%	100~400	ASTM D-1000
§. 破壞電壓Dielectric Breakdown:	kv	3.0 ↑	ASTM D-1000
§. 阻燃性Flammability :		PASS	ASTM D-568
§. RoHS檢測Rohs Test :		PASS	IEC 62321
§. VOC檢測VOC Test :		PASS	GB/T 27630
III. 庫存Storage:			
§. 條件Condition:		23°C , 50%R. H	
§. 有效期限Validity:	Year	1	

IV. 备注Remark:

*客戶須依其實際操作需求與目的, 進行產品測試與確認, 或通知本公司, 以提供進一步說明與服務

Customers need to test and confirm for the actual operational requirement and purpose or inform us to supply the further introduction service.

*本表僅供參考, 不可做為驗收標準

Above information is for reference only and should not be as inspection standard.



江苏粘博士新材料有限公司
A+Value Co., Ltd