



IF3PCLY Acetate Cloth Tape

Description : The tape is an acetate-based tape which features excellent workability, halogen-free flame resistance and single coated with a pressure sensitive acrylic-based adhesive. Conformable and easy to handle; exhibits good breaking strength, insulating and corrosion protection.

Application : Specially designed for wrapping of automotive electrical wiring harnesses wrapping, projection TV screen holding and coil holding.

Technical Details :

Properties	Units	Test Result Value	Test Method
Thickness	mm	0.20±10%	ASTM D1000
Adhesion : To steel	N/cm	2.0 ↑	ASTM D1000
To backing	N/cm	2.3 ↑	ASTM D1000
Tensile strength	N/cm	80	ASTM D1000
Elongation	%	15	ASTM D1000
Unwinding force	N/cm	1 ~ 3	ASTM D1000
Flame Resistance	class	A	(acc. to LV312)

Note : The technical data listed here should be considered representative or typical only, and should not be used for specification purposes. Customers are advised to test the material to determine the suitability against intended applications.

Color : White/Black

Flame resistance (LV312)	Class	A	B	C
	Requirement	Not flammable	Self-extinguishing	Burn Rate ≤ 100 mm/min

Dimensions : § Roll length : 10 and 25 meters.
 § Roll width : 19 mm in 10 m or 19 and 25 mm in 25 m.
 § Core : 38 mm.